

AlfaSpid Rotator "RAK"
A Re-evaluation by Don Moman VE6JY

The AlfaSpid rotator is a medium to heavy duty antenna rotator in the same general class as the HyGain TailTwister or the Yaesu G-1000 but with advanced digital features, yet priced well under these and other competing rotators. Mechanical complexity is reduced to a minimum by utilizing a simple double worm drive system. Position readout is sensed with a magnetic reed switch. The controller features digital readout and a full complement of features.

Preliminary Report and Ratings: 2002-02-11

From initial tests and experience with rotators already in the air, we expect this rotator to surpass the HyGain T2X and the Yaesu G1000, and possibly the Yaesu G2800 as well. Due to the worm drive and the excellent self braking characteristics, we feel it will survive high winds better than any of these. I have had one of these turning a 7 el 10m yagi 48 foot boom at 150 feet since the fall of 2001. It suffered no damage in winds excess of 90 km/hr recently. Another local amateur has been turning a HyGain TH-11 over three winters now, with no problems even in extreme cold temperatures. I now have one of these rotators turning a full size 3 el 40m yagi at 120 feet. I would not be testing it on this large an antenna if I did not expect it to survive.

The controller and rotator are designed to operate from a 12 volt DC source.

The rotating torque is ~1400 in lbs at 12v input (~10v at motor) and ~1740 In lbs at 18v input (~16v at motor) and 3200 with 24V

Braking torque is in excess of 9000 in lbs. This is roughly equivalent to a 200 lb person putting his full weight on the end of a 4 foot lever arm.

For Comparison:

Torque (in lbs)	Rotating	Brake
AlfaSpid Rak	3,200	>9,000
Yaesu 1000	960	5,208
TailTwister	1,000	7,000

Typical motor current draw is about 1 amp no load and 4 amps with load. The stall current increases to about 8 amps. **The unit senses that the motor is stalled and removes power after a few seconds.**

TailTwister vs AlfaSpid

I have found in the past, the T2X rotator to have enough rotating torque for most antennas, it usually fails in the brake area. It was quickly obvious the T2X was not able to lift a 25 pound weight on a 37" arm which would equal 925 in-lbs. The AlfaSpid rotator was able to pick up at least 35 pounds on a 37" arm, and with the higher voltage to the motor it lifted 47 pounds.

Watching the 2 units working gives more examples of the differences. While the DC motor slows down, it works hard and pulls more current before stalling. The AC motor in the T2X gives up much easier and just stops. The wedge brake of the T2X has problems releasing when the weight is still on it, where our worm drive doesn't have any problem holding or releasing. The

T2X often falls back until the brake finds the next notch. Keep in mind the T2X has 60 brake segments built into the brake housing so each notch equates to 6 degrees. The **AlfaSPID** rotator has a tight worm so there is only a very small backlash in the gears, I estimate it to be less than 1 degree.

Installation Features

The **AlfaSpid** rotator is designed to be mounted on a pipe mast (accepts up to ~ 2 3/8 inch mast) but adapter units are available to mount on a flat rotator plate. While we are often more used to this method of mounting – myself included – I see several advantages in the pipe mounting system. It is simple and easy to install. Many of the heavier duty commercial guyed towers are designed to support a vertical pipe and it is a simple job to adapt this to our unit. The unit can support large antennas even when mounted above the top of the tower. The 8 set bolts provide a great deal of holding power and, in my testing, were far less prone to slip than conventional U bolts. The control cable only requires 4 conductors, 2 of which should be as large as possible to reduce voltage drop to the motor.

Rotator Features:

Low voltage - high torque DC gear head motor

- Quiet and powerful self braking action with double worm drive reduction
- Real steel housing and final worm drive – not soft pot metal or cast
- Uses inexpensive 4 conductor cable
- Sealed reed switch sensor technology for reliable all weather readout
- 1 degree positioning accuracy - tight tolerances for minimal play
- Rated for large loads even when mounted outside the tower
- Designed for simple mounting to approx 2" pipe mast – both ends
- Adaptors easily be made to mate with standard bolt patterns
- Coax can pass thru center of rotator - prevents cable damage

Controller Features:

- Full selection of manual, automatic, scanning and programmable modes
- Full manual available on the internet at: <http://alfaradio.ca/>
- Digital readout with 1 degree resolution
- Large easy to read soft green LEDs
- Computer interface ability included
- Optional mouse control with 6 user programmable presets
- Low voltage DC operation from any 12 volt source (typically 2-4 amps)
- Simple optional adaptor to allow use on VERY long and/or thin cable runs
- Can be zeroed at any
- Generous over-travel in either
- Small front panel– takes up less valuable space

AlfaRadio Ltd. 11211 - 154 St., Edmonton, Alberta, Canada, T5M 1X8, 780 466 5779 Voice, 780 466 4956 Facsimile

URL: www.alfaradio.ca

~dos/spid/ALFASPID-Rotator-Spec-Short-2016-03-15.doc